

Technical Data Sheet
AISI 304 INOX FIELD TILE CANUDO 3 mm*

EN

Code	Review	Page
TS.EN.COMP.18	1	Page. 1 de 1

DESCRIPTION

Made of stainless steel, 3 mm thickness, this clamp aims to correctly fixate all the tiles of the slopes installed with the UM Canudo tile. Its shape allows an ideal overlap of 10 cm between tiles. It guarantees the reaction to the gravitational and wind sliding of the Canudo tiles, dismissing any other sealing element (masses, foams, etc.). It guarantees greater entrance and circulation of air in the roof. Due to its characteristics it is resistant to all weather, ensuring effective fastening throughout the useful life of the roof, without rusting or corroding.



Material:	AISI 304 Steel
Color:	Stainless Steel
Geometric Features:	
Length:	95 mm
Width:	13 mm
Thickness:	3 mm
Weight:	0,10 gr
Yield:	1 unit/piece

APPLICATION

The clamp should be applied to the upper part of the Canudo tile and lie on top of it, in order to promote the overlap/fastening of the subsequent tile.

Note: if the slopes have an inclination above 50% and a length of more than 4 m, the mechanical screw fixing of intermediate rows of perforated roof tile should be considered. For more information/clarifications consult the UM Canudo Application Guide or contact the UMBELINO MONTEIRO Technical Department.



* Premium solution recommended by UMBELINO MONTEIRO.